# ThinkCentre M70s Gen 3

Powerful and versatile, this small form factor desktop is designed to boost everyday productivity while saving time, effort, and desk space. It comes with up to four DDR4 (3200MHz) and up to 128GB memory support with Intel Iris X graphics, enabling seamless multitasking and work on complex data operations and graphic projects. Connect up to four displays for maximum productivity. Plus, its onboard and optional security solutions ensure optimum device and data security.




# **REASONS TO BUY**

Security features include an optional eLock, which locks the computer from the inside. preventing unauthorized removal of components and an optional smart cable clip for preventing removal of wired peripherals. Plus, onboard TPM 2.0 encrypts data end-to-end. while Kensington slot locks the device to the desk.

Despite its smaller size, this desktop has 9x USB ports, including a front-facing USB-C connector with 15W power output, that can be used for charging mobile devices.

Optional Energy Star and optional EPEAT Silver certifications ensure you save money and reduce environmental impact. Plus, it is TCO certified and comes with optional TUV low noise certified on some configurations.



MAINSTREAM COMPUTING FOR A

ThinkCentre M7 Series desktops offer enterprise security features, a wide range of configurations and expansion options, and reliability trusted by leading businesses across the globe.

# ThinkCentre M70s Gen 3

#### **KEY SPECIFICATIONS**

Processor	Up to 12th Gen Intel Core i9 processor
Operating System	Powered by Windows 11 Pro
Graphics	Intel UHD Graphics 730/770
Memory	up to 128GB DDR4-3200
Storage	Up to three drives, 1x 2.5"/3.5" HDD + 1x 2.5" HDD + 1x M.2 SSD (2.5" HDD up to 1TB each, 3.5" HDD up to 2TB, M.2 SSD up to 2TB)
Optical	
Additional Internal Bays	Optional 2.5" Bay
Expansion Slots	One PCIe 4.0 x16, low-profie Two PCIe 3.0 x1, low-profile Two M.2 slots (one for WLAN, one for SSD)
Power Supply	One of the following 180W 85%   260W 90%   310W 92%   380W 92%
Dimensions	93 x 298 x 340 mm (3.6 x 11.7 x 13.4 inches)
Weight	starting at 5.3kg (11.7lb)

#### **GREEN CERTIFICATIONS**

(Optional) EPEAT™ Gold, (Optional) EPEAT Silver, ErP Lot 3, TCO Certified 9.0, RoHS compliant

#### OTHER CERTIFICATIONS

(Optional) TÜV Rheinland Low Noise, (Optional) TÜV Rheinland Ultra Low Noise

#### CONNECTIVITY

1x serial + 1x parallel + 2x PS/2   1x parallel   1x parallel + 1x seri   1x parallel + 1x serial + 1x 2nd serial   1x serial + 1x 2nd serial   1x serial + 1x 2nd serial + 1x VGA (Flex IO)   1x serial 1x VGA (Flex IO)   1x serial + 2x USB 3.2 Gen1   2x PS/2   2x PS/2 + 1x parallel + 1x serial   2x PS/2 + 1x serial   2x PS/2 + 1x serial   2x USB 3.2 Gen1   2x USB 3.2 Gen1		
45), 1x line-out (3.5mm)  Optional Rear Ports  One of the following 1x 2nd serial + 1x serial + 1x parallel + 2x PS/2   1x DP 1.2 (Flex IO)   1x HDMI 2.0 (Flex IO)   1x VGA (Flex IO)   1x VGA (Flex IO) 1x serial + 1x parallel + 2x PS/2   1x parallel   1x serial + 1x serial + 1x serial   2x PS/2   2x PS/2 + 1x serial   2x PS/2 + 1x Serial	Front I/O	, , , , , , , , , , , , , , , , , , , ,
1x 2nd serial + 1x serial + 1x parallel + 2x PS/2   1x DP 1.2 (Flex IO)   1x HDMI 2.0 (Flex IO)   1x VGA (Flex IO)   1x VGA (Flex IO)   1x VGA (Flex IO)   1x vGA (Flex IO)   1x serial + 1x parallel + 2x PS/2   1x parallel   1x serial   1x VGA (Flex IO)   1x serial + 2x USB 3.2 Gen1   2x PS/2   2x PS/2 + 1x parallel + 1x serial   2x PS/2 + 1x serial   2x PS/2 + 1x serial   2x USB 3.2 Gen1   1x USB-C (Flex IO)   2x USB 3.2 Gen1 + 1x USB-C (Flex IO)   2x USB 3.2 Gen1 + 1x serial + 1x parallel + 2x PS/2  WLAN + Bluetooth  One of the following Intel 9560 11ac, 2x2 + BT5.0   Intel AX201 11ax, 2x2 + BT5.1   RTL8822CE 11ac, 2x2 + BT5.0   RTL8852BE 11ax, 2x2 + BT5.1  Ethernet  One of the following BN8E88 + Integrated 100/1000M   Integrated 100/1000M   RTL8125BGS 2.5G + Integrated 100/1000M   RTL8168H +	Rear I/O	
Intel 9560 11ac, 2x2 + BT5.0   Intel AX201 11ax, 2x2 + BT5.1     RTL8822CE 11ac, 2x2 + BT5.0   RTL8852BE 11ax, 2x2 + BT5.1     Ethernet	Optional Rear Ports	1x 2nd serial + 1x serial + 1x parallel + 2x PS/2   1x DP 1.2 (Flex IO)   1x HDMI 2.0 (Flex IO)   1x VGA (Flex IO)   1x VGA (Flex IO)   1x serial + 1x parallel + 2x PS/2   1x parallel   1x parallel + 1x seria   1x parallel + 1x serial + 1x 2nd serial   1x serial   1x serial + 1x 2nd serial   1x VGA (Flex IO)   1x serial + 1x VGA (Flex IO)   1x serial + 1x VGA (Flex IO)   1x serial + 2x USB 3.2 Gen1   2x PS/2   2x PS/2 + 1x parallel + 1x serial   2x PS/2 + 1x serial   2x PS/2 + 1x Serial + 2x USB 3.2 Gen1   2x USB 3.2 Gen1   2x USB 3.2 Gen1 + 1x USB 3.2 Gen1 + 1x HDMI 2.0 (Flex IO)   2x USB 3.2 Gen1 + 1x USB-C (Flex IO)   2x USB 3.2 Gen1 + 1x parallel + 2x USB 3.2 Gen1 + 1x parallel + 2x USB 3.2 Gen1 + 1x USB-C (Flex IO)   2x USB 3.2 Gen1 + 1x USB-C (Flex IO)   2x USB 3.2 Gen1 + 1x parallel + 2x
BN8E88 + Integrated 100/1000M   Integrated 100/1000M   RTL8125BGS 2.5G + Integrated 100/1000M   RTL8168H +	WLAN + Bluetooth	Intel 9560 11ac, 2x2 + BT5.0   Intel AX201 11ax, 2x2 + BT5.1
	Ethernet	BN8E88 + Integrated 100/1000M   Integrated 100/1000M   RTL8125BGS 2.5G + Integrated 100/1000M   RTL8168H +

#### SECURITY & PRIVACY

Chassis Intrusion Switch E-Lock No E-Lock

Discrete TPM 2.0, TCG certified, (Optional) E-lock, (Optional) Smart Cable Clip, Kensington® Security Slot, Padlock Loop

#### MANAGEABILITY

Non-vPro vPro Essential

Information presented here may represent the maximum possible configurations for this product, but it does not necessarily reflect what is available in your region. Please ask your rep or check the specifications for specific Part Numbers in your region. © 2022 Lenovo. Products are available while supplies last. Lenovo is not responsible for photographic or typographic errors. Lenovo, the Lenovo logo, ThinkPad, ThinkCentre, ThinkBook, ThinkStation and ThinkVision are trademarks or registered trademarks of Lenovo. 3rd party product and service names may be trademarks of others. Depending on factors such as the processing capability of peripheral devices, file attributes, system configuration and operating environments, the actual data transfer rate of USB connectors will vary and is typically slower than published standards.

# Recommended for this device



### ThinkVision T23i-20

23" FHD (1920x 1080) monitor with 75% NTSC colour gamut and anti-glare coating

1x HDMI, 1x DisplayPort, 1x VGA, 4x USB3.2, 1x USB3.2 Type-B upstream, audio out

Lift, Tilt, Pivot, Swivel stand for enhanced viewing comfort, plus a conveniently placed integrated smartphone holder in the base.



# ThinkVision T24v-20

23.8" FHD (1920x1080) monitor with 72% NTSC colour gamut & anti-glare coating

1x HDMI, 1x DisplayPort, 1x VGA, 2x USB3.2, 1x USB 3.2 Type-B upstream, audio out

Angle-adjustable InfraRed webcam supporting Windows Hello



# **On-site Service**

If a problem can't be fixed remotely, we will visit your location

Normally next business day service

Agreed appointment times